STORM WATER FACILITY AGREEMENT

THIS AGREEMENT, is made and entered into this 10th day of	JUNE , 2072, by
and between DESIGN BUILD CONTRACTORS, INC.	(hereinafter referred to
as "Owner", and American Fork City (hereinafter referred to as the "C	ity"), a Municipal
Corporation.	

RECITALS

WHEREAS, the Owner desires to improve, develop or redevelop real property located at approximately 960 5. in American Fork City, Utah County, State of Utah (hereinafter referred to as the "Property"), which is more particularly described in Exhibit A attached hereto;

WHEREAS, said development requires the installation and maintenance of storm water facilities (hereinafter referred to as "Facilities") to be constructed according to designs and plans approved by the City;

WHEREAS, the Owner, for and in behalf of its administrators, executors, successors, heirs, or assigns, including any homeowners association, recognizes and agrees that the health, safety, and welfare of the citizens of the City require that the Facilities be constructed and adequately maintained on the Property throughout the life of the development; and

NOW, THEREFORE, in consideration of the foregoing, the mutual covenants contained herein, and the following terms and conditions, the parties hereto agree as follows:

SECTION 1 FACILITIES

Facilities include all storm water detention and control structures, flood control devices, or other improvements, which may include, but is not limited to all pipes, channels, or other structures and infrastructure built to convey storm water to the Facilities, as well as all structures, improvements, and vegetation provided to control the quantity and quality of the storm water which are required by the City in the site plan attached hereto as Exhibit B.

SECTION 2 FACILITIES CONSTRUCTION

The Owner shall, at its sole cost and expense, construct the Facilities in accordance with the plans and specifications for the development approved by the City. Owner understands and agrees that modifications may be needed to make the system work properly after the Facilities are installed and agrees to make modifications and adjustments as may be necessary and required by the City.



SECTION 3 MAINTENANCE

The Owner shall, at its sole cost and expense, adequately maintain the Facilities in good working condition acceptable to the City and in accordance with the schedule of long term maintenance activities agreed to by the parties and attached hereto as Exhibit C. Adequate maintenance is herein defined as follows: 1) keeping the Facilities in good working condition so that the Facilities are performing their design functions, 2) performing facility inspections and repairs as may be needed, and 3) replacing and/or modifying portions, or all of the system, as may be needed to maintain the intended function of the facility.

SECTION 4 EASEMENT

The Owner hereby grants permission to the City, its authorized agents, and employees to enter upon the Property and to inspect the Facilities whenever the City deems it necessary. Whenever possible, the City shall provide notice prior to entry. Inspections by the City shall be conducted in a reasonable manner and at reasonable times, as determined appropriate by the City. The purpose of the inspection shall be to determine and ensure that the Facilities are being adequately maintained, are continuing to perform in an adequate manner, and are in compliance with all laws, regulations, and approved plans and specifications. The Owner hereby grants a twenty-five (25) foot access easement in favor of the City with the midpoint of the easement lying over the midpoint of the Facilities identified in the attached plan. This easement shall be limited in scope to allow only those actions which are necessary to allow the City to inspect, ensure adequate maintenance, and to cause any repairs to be made that the City deems necessary. This easement shall include, but is not be limited to, prohibiting the construction of structures or improvements that would impact or obstruct the intended purposes of the Facilities or restrict the ability of the Owner or the City to inspect, maintain, or repair the Facilities.

SECTION 5 FAILURE TO MAINTAIN FACILITIES

In the event the Owner fails to maintain the Facilities in good working order acceptable to the City and in accordance with the maintenance schedule incorporated in this Agreement, the City, in addition to any other remedies provided by State or City code, may, with due notice as provided in Section 6, enter the property and take whatever steps it deems necessary to return the Facilities to good working order. This provision shall not be construed to allow the City to erect any structure of a permanent nature on the property that is not included in the plans and specifications for the development, or other agreement between the parties. It is expressly understood and agreed that the City is under no obligation to maintain or repair the Facilities. The decision to maintain or repair the Facilities shall be at the City's sole discretion and in no event shall this Agreement be construed to impose any such obligation on the City or to create any liability for the City refusing to undertake such a duty.

SECTION 6 NOTICE OF DEFICIENCIES

If the City finds that the Facilities contain any defects or are not being maintained adequately, the City shall provide Owner written notice of the defects or deficiencies and provide Owner with a reasonable time, as determined by the City, to cure such defects or deficiencies.

SECTION 7 RECOUPMENT OF COSTS

In the event the City performs work of any nature pursuant to the Agreement, or expends any funds in the performance of said work for labor, use of equipment, supplies, materials, and the like, the Owner shall reimburse the City within thirty (30) days of receipt thereof for all the costs incurred by the City. If not paid within the prescribed time period, the City shall be entitled to record a lien against the real property in the amount of such costs. The actions described in this section are in addition to and not in lieu of any and all legal remedies available to the City as a result of the Owner's failure to maintain the Facilities.

SECTION 8 LIMITATION OF LIABILITIES

It is the sole intent of this Agreement to insure the proper construction and maintenance of the Facilities by the Owner. As the Facilities are not part of the City's Storm Water Collection System, this agreement does not create or extend any rights to immunity or liability protections provided by law to municipalities. This Agreement shall not be deemed to create or affect any additional liability of any party for damage alleged to result from or caused by storm water runoff, or to constitute a waiver of any immunity provided to the City through the Utah State Code or Constitution.

SECTION 9 SEDIMENT ACCUMULATION

Adequate maintenance shall include control of sediment accumulation resulting from the normal operation of the Facilities. The Owner will make accommodations for the removal and appropriate disposal of all accumulated sediments.

SECTION 10 REQUIREMENTS AND STANDARDS

The Parties agree to follow and comply with all requirements applicable to storm water detention and control facilities as by the Utah Department of Environmental Quality, Division of Water Quality, including the Small MS4 General UPDES Permit requirements, and by the City ordinances and Storm Water Management Plan as existing at the time of executing this agreement and as may be amended from time to time. The parties agree that these requirements and regulations are incorporated herein by this reference and that this agreement shall be deemed

automatically amended to incorporate any and all changes and amendments made thereto after the signing of this agreement.

SECTION 11 INSPECTIONS

The Owner shall perform an annual inspection of the Facilities. The City may require more frequent inspections should it have reason to believe that such inspections are necessary. All inspections shall be conducted by a qualified inspector and the results shall be reported to the City. The purpose of the inspection and reporting is to assure safe and proper functioning of the Facilities, including but not limited to, the structural improvements, berms, outlet structure, pond areas, access roads, vegetation, landscaping, etc. All annual inspection reports shall be submitted to the City Public Works Department no later than September 1 of any given year and shall be on the Maintenance Inspection Report attached hereto as Exhibit D.

SECTION 12 INDEMNITY

The Owner indemnifies and holds harmless the City and its authorized agents and employees for any and all damages, accidents, casualties, occurrences or claims which might arise or be asserted against the City from the construction, presence, existence or maintenance of the facility or facilities by the Owner. In the event a claim is asserted against the City, its authorized agents or employees, the City shall promptly notify the Owner and the Owner shall defend at its own expense any suit based on such claim. If any judgment or claims against the City, its authorized agents or employees shall be allowed, the Owner shall pay for all costs and expenses in connection herewith.

SECTION 13 COVENANT RUNNING WITH THE LAND

This Agreement shall be recorded at the Utah County Recorder's Office and shall constitute a covenant running with the land and shall be binding on the Owner, its administrators, executors, heirs, assigns and any other successors in interest, including any homeowners association.

SECTION 14 REMEDIES

This Agreement may be enforced by proceedings at law or in equity by or against the parties hereto and their respective successors in interest. Any rights or remedies contained in this Agreement shall be in addition, and non-exclusive, to any rights existing under the Utah Code or that may exist under the common law.

SECTION 15 ATTORNEYS FEES

If any party retains, consults, or uses an attorney because of any breach, default, or failure to perform as required by this Agreement, the non-breaching/defaulting party shall be entitled to reasonable attorney's fees incurred before litigation is filed. In the event that any litigation is commenced to enforce or interpret this Agreement the prevailing party shall be entitled to its attorneys fees, expert witness expenses, and litigation related expenses, including but not limited to court costs.

SECTION 16 THIRD PARTY BENEFICIARIES

This Agreement shall be binding upon and inure solely to the benefit of the parties herein and is not intended to create contractual rights in any third party.

SECTION 17 NO PARTNERSHIP

Nothing contained in this Agreement shall be deemed to create any form of a partnership or joint-venture between the City and Owner.

SECTION 18 UTAH LAW AND VENUE

This Agreement shall be interpreted pursuant to the laws of the State of Utah. Any and all suits for any claims or for any and every breach or dispute arising out of this Agreement shall be maintained in the appropriate court of competent jurisdiction in Utah County, Utah.

SECTION 19 INTEGRATED AGREEMENT

This Agreement sets forth the entire agreement of the parties and supersedes all prior agreements, whether written or oral, that exists between the parties regarding the subject matter of this Agreement.

SECTION 20 SEVERABILITY

The provisions of this agreement shall be severable and if any phrase, clause, sentence or provision is declared unconstitutional, or the applicability thereof to the, its successors and assigns, is held invalid, the remainder of this Covenant shall not be affected thereby.

SECTION 21 AMENDMENTS

Except as expressly provided elsewhere in this Agreement, no provision of this Agreement may not be modified except in writing agreed to by both parties.

IN WITNESS WHEREOF, the parties hereto have executed this Agreement on the dates set forth below.

	OWI	NER	9	
Date: June	13,2022.	Ched	Yang	<u> </u>
		By: <u>CHAT</u> Its: <u>Ohwe</u>	Young B	·
	NOTARI	ZATION		
TATE OF UTAH)):ss			
OUNTY OF UTAH	,		ŧ	
ne above Agreement was of hat Yung when identified in the above	ve signed Agreement	. In executing this	Agreement, the s	ioner did
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750		n the agreement on		
NOTARY PUBLIC SCOTT M ROBERTS		n the agreement on	behalf of the Ow	
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750 MY COMMISSION EXPIRES APRIL 30, 2024 STATE OF UTAH	luly authorized to sign	n the agreement on	behalf of the Ow	
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750 MY COMMISSION EXPIRES APRIL 30, 2024 STATE OF UTAH	luly authorized to sign AMERICAN	n the agreement on	Ham We PUBLIC	
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750 MY COMMISSION EXPIRES APRIL 30, 2024 STATE OF UTAH Pate: Jane	luly authorized to sign AMERICAN	The agreement on NOTAF FORK CITY Scott Sensanba	Ham We PUBLIC	
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750 MY COMMISSION EXPIRES APRIL 30, 2024	luly authorized to sign AMERICAN	The agreement on NOTAF FORK CITY Scott Sensanba	Ham We PUBLIC	
NOTARY PUBLIC SCOTT M ROBERTS COMM. # 711750 MY COMMISSION EXPIRES APRIL 30, 2024 STATE OF UTAH Pate: Jane	luly authorized to sign AMERICAN	The agreement on NOTAF FORK CITY Scott Sensanba	Ham We PUBLIC	

Exhibit A

EXHIBIT A

A portion of Parcel #13:040:0185

Rockwell Ranch Block 8 Plat

Beginning at a point being North 89°59'22" East 1,811.54 feet along section line and South 46.75 feet from the West Quarter Corner of Section 22, Township 5 South, Range 1 East, Salt Lake Base and Meridian; and running

thence Northwesterly 23.61 feet along the arc of a 15.00 foot radius curve to the right (center bears North 00°35'46" East and the chord bears North 44°18'37" West 21.24 feet with a central angle of 90°11'14");

thence North 00°11'49" West 54.12 feet;

thence East 327.71 feet;

thence South 01°17'45" West 72.64 feet;

thence North 89°23'31" West 311.06 feet to the point of beginning.

Contains 23,119 Square Feet or 0.531 Acres

Rockwell Ranch – Block 8

Slope Easement

Beginning at a point being North 89°59'22" East 1,796.52 feet along section line and North 22.57 feet from the West Quarter Corner of Section 22, Township 5 South, Range 1 East, Salt Lake Base and Meridian; and running

thence North 86°22'51" East 61.77 feet; thence North 88°22'50" East 50.44 feet; thence North 89°55'00" East 61.90 feet; thence South 89°20'47" East 64.76 feet; thence North 84°57'56" East 33.14 feet; thence North 89°25'27" East 21.92 feet; thence South 87°12'06" East 28.78 feet; thence North 54°51'32" East 7.51 feet; thence South 42°09'12" East 9.98 feet; thence South 07°02'09" East 26.42 feet; thence South 05°08'32" West 41.85 feet; thence South 47°08'35" West 11.82 feet; thence North 01°17'45" East 72.64 feet; thence West 327.71 feet to the point of beginning.

Contains 2,354 Square Feet or 0.054 Acres

Exhibit B

EXHIBIT B

Long-Term Stormwater Management Plan

for:

Rockwell Ranch Block 8 – Phase 1 960 West 350 South American Fork City, Utah, 84003

PURPOSE AND RESPONSIBILTY

As required by the Clean Water Act and resultant local regulations, including American Fork City Municipal Separate Storm Sewer Systems (MS4) Permit, those who develop land are required to build and maintain systems to minimize litter and contaminants in stormwater runoff that pollute waters of the State.

This Long-Term Stormwater Management Plan (LTSWMP) describes the systems, operations and the minimum standard operating procedures (SOPs) necessary to manage pollutants originating from or generated on this property. Any activities or site operations at this property that contaminate water entering the City's stormwater system and generate loose litter must be prohibited, unless SOPs are written to manage those activities or operations, and amended into this LTSWMP.

The project discharges into adjacent public streets that are routed to a detention basin with discharges into ditches and eventually finds its way to Utah Lake. Based on information provided by the Utah Department of Environmental Quality Utah Lake is identified as being impaired due to excess total phosphorus. The LTSWMP is aimed at addressing these impairments in addition to all other pollutants that can be generated by this property.

CONTENTS

SECTION 1: SITE DESCRIPTION, USE AND IMPACT

SECTION 2: TRAINING

SECTION 3: RECORDKEEPING

SECTION 4: CONTACT INFORMATION

SECTION 5: APPENDICES

SECTION 1: SITE DESCRIPTION, USE AND IMPACT

The site infrastructure at our site is limited at controlling and containing pollutants and our operations if managed improperly can contaminate the environment. This LTSWMP includes standard operations procedures (SOP)s that are intended to compensate for the pollution containment limitations of our site infrastructure and direct our maintenance operations to responsibly manage our grounds.

If or when SOPs change or are updated the city will be notified.

Parking, Sidewalk and flatwork

The site consists of private alleys, driveways, and sidewalks that tie to proposed buildings and adjacent public roadways. These hardscape surfaces if not kept property clean can impact stormwater quality.

Any sediment, leaves, debris, spilt fluids or other waste that collects on our parking lots and sidewalks will be carried by runoff to our storm drain inlets. This waste material will settle in our storm drain system increasing maintenance cost and solid and dissolved waste in our runoff can pass through our system ultimately polluting Utah Lake. Maintenance involves regular sweeping, but it can also involve pavement washing to remove stains, slick spots and improve appearance when necessary. Use our Pavement Maintenance and the Pavement Washing SOPs to manage pollutants that collect on our pavements.

Landscaping

Our landscape operations can result in grass clippings, sticks, branches, dirt, mulch, fertilizers, pesticides and other pollutants to fall or be left on our paved areas. This waste material will settle in our storm drain system increasing maintenance cost and solid and dissolved waste in our runoff can pass through our storm drain system ultimately polluting Utah Lake. The primary pollutant impairing Utah Lake is organic material so it is vital that our paved areas with direct connection to the City storm drain systems remain clean of landscape debris.

Use our Landscape Maintenance SOP to prevent this potential pollution source from affecting the Utah Lake.

Storm Drain System

The storm drain inlets direct all runoff to public streets that are eventually routed through an offsite detention basin and though a stormwater treatment unit that is designed to capture floating material and heavier sediment particles, but does not trap suspended or dissolved pollutants. This device is susceptible to bypass and scour during large storm events and the dissolved pollutants will pass through and harm Utah Lake. Also, our stormwater treatment system holds water that can breed mosquitoes. It is important to regularly maintain this system to protect Utah Lake and prevent mosquito breeding. Use our Storm Drain Maintenance SOP manage our storm drain system responsibly.

Waste Management

Each condominium unit and townhome unit within the project will have their own individual dumpster. Good waste management systems, if managed improperly, can become the source of the very pollution that they were intended to control. Use our Waste Management SOP to control and manage the solid waste we generate.

Snow and Ice Removal Management

Salt is a necessary pollutant and is vital to ensuring a safe parking and pedestrian walkways. However, the snow removal operations if improperly managed will increase our salt impact to our own vegetation and local water resources. Use our Snow and Ice Removal SOP to minimize our salt impact.

SECTION 2: TRAINING

Ensure that all employees and maintenance contractors know and understand the SOPs specifically written to manage and maintain the property. Maintenance contractors must use the stronger of their Company and the LTSWMP SOPs. File all training records in Appendix C.

SECTION 3: RECORDKEEPING

Maintain records of operation and maintenance activities in accordance with SOPs. Mail a copy of the record to American Fork City Stormwater Division annually.

SECTION 4: CONTACT INFORMATION.

HOA

Rockwell Ranch Master Owners Association, Inc. 520 South 850 East, Suite A300, Lehi, Utah 84043.

Contact: TBD

Developer

White Horse Developers 520 South 850 East, Suite A4 Lehi, Utah 84043

Contact: Jake Horan (801) 362-8420

Long-Term Stormwater Management Plan Rockwell Ranch Block 8 – Phase 1

SECTION 5: APPENDICES


Appendix A- Site Drawings and Details Appendix B- SOPs Appendix C- Recordkeeping Documents


Long-Term Stormwater Management Plan Rockwell Ranch Block 8 – Phase 1

APPENDIX A – SITE DRAWINGS AND DETAILS

43







MANGEMENT PLAN

THE VILLAS AT ROCKWELL RANCH BLOCK 8


960 WEST 350 SOUTH AMERICAN FORK, UTAH 84003



SALT LAKE CITY
43W, 10005, Sade 500
5 sed, 101 4000
5 sed, 101 4000
Fhore 301 550 5020
LAYY00
Fhore 301 550 1100
TOOGLE
Fhore 63963 633
RICHFIELD
Fhore 45963 633
RICHFIELD
Fhore 45963 633








O DESCRIPTION CONTROLLED DE SECURIO.

O DESCRIPTION DE SECURIO DE SECURIO DE SECURIO.

O DESCRIPTION DE SECURIO DE SECURI



ာ	1000 1000 1000 1000 1000 1000	STE PLA	2
100	A STORE OF THE PERSON NAMED IN COLUMN NAMED IN	· -	REVEN


THE VILLAS AT ROCKWELL RANCH BLOCK 8

960 WEST 350 SOUTH AMERICAN FORK, UTAH 84003




SALT LANG CITY
65N 10005 5 540 500
5act), IT 60070
Paul. 801.25 0529
LATTON
Phone 801.55 7 1100
TOOBLE
Phone 405 881 3500
CEDAR CITY
Phone 405 888 2801
Phone 405 888 2801














C-200	CRADING AND DRABIAGE PLAN	CARENER
-------	------------------------------	---------


THE VILLAS AT ROCKWELL RANCH **BLOCK 8**

960 WEST 350 SOUTH AMERICAN FORK, UTAH 84003

_		-	
	HATE HOUSE OWNER, OWNER AND INCHINE MEDICAL COMMENTS OF STREET AND	1	TOMBHOUSHIEL MANA







Transiero, les con la securio in le compleximanea de la compleximanea del compleximanea de la compleximanea del compleximanea de la compleximanea del compleximanea dela

ER O AN COMMUNICADE AUSSIANCH STORM DESCRIPTION ET ENTRE EN SERVICION EN LA COMPONICADA SERVICIO PRICOCA COMPONICADA SERVICIONAL SERVICION

ASSESSMENT OF THE PROPERTY OF

ORRENA C-300 THE VILLAS AT ROCKWELL RANCH BLOCK 8

960 WEST 350 SOUTH AMERICAN FORK, UTAH 84003 THE PARK DESIGNED
SE SUPERIOR DESIGNED
SE SUPERIOR DE SUPERIOR
SE SUPERIOR DE SUPERIOR
DE SUPERIOR
PROFE SE SESSO


LAYTON
Phone 801547;100
TOOELE
Phone 435.843.590
CEBAR CITY
Phone 435.865;163
RICHFIELD
Phone 435.965 283

THE STANDARD IN SIGNED BY

SALT LAKE CITY
6 W, 10000 S, Suda 500

Sardy, UT 64070


Phone 801 255 0529











EDOSON CONTROL PU

THE VILLAS AT ROCKWELL RANCH BLOCK 8

> 960 WEST 350 SOUTH AMERICAN FORK, UTAH 84003



LAYTON
Phon. 801 S47.1100
TOOELE
Phon. 405 843 3590
CEDAR CITY
Phon. 405 805 1433
RICHFIELD
Phone. 405 886 2863


ENSIGN


THE STANDARD MERCENERGY


SALT LANCE CITY


SAMY, UROUS, SAMS 500


SAMY, UROUS, UROUS,




























THE VILLAS AT ROCKWELL RANCH BLOCK 8











Long-Term Stormwater Management Plan Rockwell Ranch Block 8 – Phase 1

APPENDIX B - SOPs

Pavement Maintenance Operations

General:

These SOPs are not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in these SOPs.

1. Purpose and Selection:

- a) Reduce stormwater pollution by sweeping and removing pollutants that will be carried to City stormwater systems during stormwater runoff or by non stormwater runoff.
- b) The sweeper is intended for removing material that collect on pavements by use and the natural degradation of pavements, ie. material that collect, drop from vehicles and the natural erosion and breaking up of pavements.

2. Regular Procedure:

- a) Remain aware of debris and sweep minor debris as needed by hand.
- b) Generally sweeping machinery should be used during autumn when leaf fall is heavy and early spring after winter thaw. Sometimes sweeping machinery will be necessary when accumulations are spread over a large area of the pavement.
- c) HOA roadways, driveways, and other hardscape areas will be swept.
- d) Manage outside activities that leave waste or drain pollutants to our pavements. This involves outside functions including but not limited to: Yard sales, yard storage, fund raisers, etc. Do not allow car wash fund raiser or other activities that allow detergents or other pollutants to be wash into storm drain systems.

4. Disposal Procedure:

- a) Service contractor dispose at licensed facilities
- b) Dispose of hand collected material in dumpster

5. Training:

Landscape Maintenance Operations

General:

This SOP is not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in this SOP.

Rule: Prevent any solids, liquids or any light weight material from being carried away from the construction or maintenance envelop by wind or water.

1. Application:

a) This SOP should provide sufficient direction for many of the general landscaping operations, e.g., fertilizer and pesticide applications, mowing, weeding, tree trimming, digging, sprinkler repairs, varying landscape cover management, etc.

2. Maintenance Procedure:

- a) Grooming
 - Lawn Mowing Immediately following operation sweep or blow clippings onto vegetated ground.
 - Fertilizer Operation Prevent overspray. Sweep or blow fertilizer onto vegetated ground immediately following operation.
 - Pesticide Operations Prevent overspray, use spot treatment, sweep or blow dry pesticide onto vegetated ground immediately following operation.
- b) Remove or contain all erodible or loose material prior forecast wind and precipitation events, before any non-stormwater will pass through and over the project site and at end of work period. Light weight debris and landscape materials can require immediately attention when wind expected.
- c) Landscape project materials and waste can usually be contained or controlled by operational best management practices.
 - Operational; including but not limited to:
 - Strategic staging of materials eliminating exposure, such as not staging on pavement
 - > Avoiding multiple day staging of landscaping backfill and spoil on pavements
 - > Haul off spoil as generated or daily
 - > Scheduling work when weather forecast are clear.

d) Cleanup:

- Use dry cleanup methods, e.g. square nose shovel and broom and it is usually sufficient when no more material can be swept onto the square nosed shovel.
- Power blowing tools

3. Waste Disposal:

a) Dispose of waste according to General Waste Management SOP, unless superseded by specific SOPs for the operation.

4. Equipment:

- a) Tools sufficient for proper containment of pollutants and cleanup.
- b) Push broom and square blade shovel should be a minimum.

5. Training:

- a) Annually and at hire
- b) Landscape Service Contractors must have equal or better SOPs.

Waste Management Operations

General:

This SOP is not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in this SOP.

1. Application:

a) This SOP is intended for all Staff, intended for the proper disposal of common everyday waste.

2. Waste Collection.

- a) Regularly inspect and look for garbage, trash, and debris on-site including the detention pond and grounds. Collect and properly dispose of it.
- b) At winter time, inspection and collection will be done at fall during winterization and at spring time when the first cut occurs. The rest of the time it will be done weekly at same time as the cutting.

3. Waste Collection Devices (Exposed units):

- a) The site contains 2 types of waste management containers.
 - 6yd dumpster with lid
 - Receptacles with lids

4. Waste Disposal Restrictions for all waste Scheduled for the Intermountain Regional Landfill:

- a) Generally most waste generated at this property, and waste from spill and clean up operations can be disposed in our dumpsters under the conditions listed in this SOP. Unless other disposal requirements are specifically identified by the product SDS or otherwise specified in other SOPs.
- b) Know the facility disposal requirements and restrictions. It should not be assumed that all waste disposed in collection devices will be disposed at the Intermountain Regional Landfill.
- c) Review Intermountain Regional Landfill regulations for additional restrictions and understand what waste is prohibited in the Intermountain Regional Landfill. Ensure the SDS and Intermountain Regional Landfill regulations are not contradictory.

Generally the waste prohibited by the Intermountain Regional Landfill is:

- ➤ Liquid:
 - paint
 - pesticides/fertilizers

- oil (all types)
- antifreeze
- batteries
- liquid chemicals
- etc.

(Generally, all the above hazardous waste when involved in minor spill cleanup operations can be disposed in covered dumpsters and our waste bays, if the liquid is contained in absorbent material, e.g. sand, dirt, loose absorbent, pads, booms etc., and transformed or dried such that it will not drip. This is not intended for whole sale disposal of out dated or spent liquid hazardous waste. When disposal of out dated or spent liquid is needed or for questions of how to dispose of other waste, contact the Utah County Health Department for instructions and locations, (801-851-7331).

5. Waste Disposal Required for Intermountain Regional Landfill or other:

- a) Generally for waste not accepted by the Intermountain Regional Landfill.
- b) Follow SDS for disposal requirements. Review Intermountain Regional Landfill regulations for additional restrictions and understand what waste is prohibited in the Intermountain Regional Landfill. Ensure the SDS and Intermountain Regional Landfill regulations are not contradictory General rules are:
 - Get approval prior to delivery.
 - Transport waste in secure leak proof containers that are clearly labeled.
- c) Lookup and follow disposal procedures for disposal of waste at other EPA approved sites, the Intermountain Regional Landfill # is a good resource, (801) 930-0984

6. General Staff Maintenance Practices:

- a) Prevent dumpsters and receptacles from becoming a pollution source by:
 - 1. Closing lids
 - 2. Reposition tipped receptacles upright.
 - Report full or leaking and unsecured dumpsters and receptacles to the company provider or repair it in house. Determine source liquids and prevent it.
 - 4. Report any eminent pollutant hazard related to dumpsters and receptacles to the owner.

6. Training:

Storm Drain Maintenance Operations

General:

These SOPs are not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in these SOPs.

1. Procedure:

- a) Inspect for need:
 - 1. Schedule cleaning for boxes and pipe that contain 2" or more of sediment and debris.
 - 2. Remove debris by vacuum Intermountain Regional Landfill operated machinery.
 - 3. When accumulations are mostly floating debris this material can be removed with a net.
 - 4. Inspect standing water for mosquito larvae and contact Utah County Health Department Mosquito Abatement when necessary.
 - 5. Inspect at time of winterization.

2. Disposal Procedure:

- a) Dispose of waste collected by machinery at regulated facilities.
- b) Floating materials and floating absorbent materials may be disposed in dumpster when dried out. Dry dirt and slurry may also be disposed in the dumpster.
- c) Disposal of hazardous waste
 - 1. Dispose of hazardous waste at regulated disposal facilities, see Waste Management and Spill Control SOP
- d) Disposal of waste collected from storm drain device at regulated facilities.
 - 1. UniStorm Stormwater Treatment System is installed with this development and the recommended maintenance practice for the UniStorm System is to plan on quarterly inspections and an annual pump-out. See *Appendix C* for manufacturer's recommendations.

3. Training:

Pavement Washing Operations

General:

These SOPs are not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in these SOPs.

1. Procedure:

- a) Prevent waste fluids and any detergents if used from entering storm drain system. The following methods are acceptable for this operation.
 - Dam the inlet using a boom material that seals itself to the pavement and pick up the wastewater with shop-vacuum or absorbent materials.
 - Collect wastewater with shop-vacuum simultaneous with the washing operation.
 - Collect wastewater with vacuum truck or trailer simultaneous with the washing operation.
- b) This procedure must not used to clean the initial spills. First apply the Spill Containment and cleanup SOP.

2. Disposal Procedure:

- a) Small volumes can usually be drained to the local sanitary sewer. Contact the Timpanogos Special Service District.
- b) Large volumes must be disposed at regulated facilities.

2. Pavement Cleaning Frequency:

a) There is no regular pavement washing regimen. Pavement washing is determined by conditions that warrant it, including but not limited to: prevention of slick or other hazardous conditions or restore acceptable appearance of pavements.

3. Training:

Snow and Ice Removal Management

General:

This SOP is not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in this SOP.

1. Application:

a) Parking and sidewalk winter management operations.

2. De-Icing Procedure:

- a) Do not store or allow salt or equivalent to be stored on outside paved surfaces. Storage of salt or other de-icing agents will be the responsibility of the snow and ice service contractor.
- b) Minimize salt use by varying salt amounts relative to hazard potential.
- c) Sweep excessive piles left by the spreader.
- d) Store snow in designated snow storage easements per TOD code. See *Appendix A* Site drawings and details for location of snow storage easements.
- e) Watch forecast and adjust salt amounts when warm ups are expected the same day.

3. Training:

- a) Annually and at hire.
- b) Require snow and ice service contractors to follow the stronger this SOP and their company SOPs.

General Construction Maintenance

General:

This SOP is not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in this SOP.

Rule: Prevent any solids, *liquids or any light weight material from being carried away from the construction or maintenance envelop by wind or water.

*liquids - including culinary water and irrigation water that are polluted with material that will damage the environment.

1. Application:

a) This SOP should provide sufficient direction for many of the general operations, e.g., building maintenance, curb/sidewalk/flatwork, overlay/patching, landscape renovations, misc. maintenance/repairs, etc.

2. Construction Procedure:

- a) Remove or contain all erodible or loose material prior forecast wind and precipitation events or before non-stormwater will pass through the project site. For light weight debris maintenance can require immediately attention for wind events and many times daily maintenance or as needed for precipitation or nonstormwater events.
- b) Project materials and waste can be contained or controlled by operational or structural best management practices.
 - Operational; including but not limited to:
 - > Strategic staging of materials eliminating exposure, such as not staging on pavement
 - > Avoiding multiple day staging of backfill and spoil
 - > Haul off spoil as generated or daily
 - > Schedule work during clear forecast
 - Structural; including but not limited to:
 - > Inlet protection, e.g. wattles, filter fabric, drop inlet bags, boards, planks
 - > Gutter dams, e.g. wattles, sandbags, dirt dams
 - > Boundary containment, e.g. wattles, silt fence
 - Dust control, e.g. water hose,
 - Waste control, e.g. construction solid or liquid waste containment, dumpster, receptacles

- c) Inspect often to insure the structural best management practices are in good operating condition and at least prior to the workday end. Promptly repair damaged best management practices achieving effective containment.
- d) Cleanup:
 - Use dry cleanup methods, e.g. square nose shove and broom.
 - Wet methods are allowed if wastewater is prevented from entering the stormwater system, e.g. wet/dry vacuum, disposal to our landscaped areas.
- e) Cleanup Standard:
 - When a broom and a square nosed shovel cannot pick any appreciable amount of material.

3. Waste Disposal:

- a) Dispose of waste according to General Waste Management SOP, unless superseded by specific SOPs for the operation.
- b) Never discharge waste material to storm drains

4. Equipment:

- a) Tools sufficient for proper containment of pollutants and cleanup.
- b) Push broom and square blade shovel should be a minimum.

5. Training:

Spill Control

General:

This SOP is not expected to cover all necessary procedure actions. Operators are allowed to adapt SOPs to unique site conditions in good judgment when it is necessary for safety, and the proper, and effective containment of pollutants. However, any changes of routine operations must be amended in this SOP.

1. Rational:

a) All properties are susceptible to spills whether it is a result of operations or by customers. Insufficient response, inadequate containment materials and improper spill cleanup methods will result in pollutants in our waterways. Once the pollutants reach our storm drain system, or even the detention pond, they are difficult and expensive to remove.

2. Containment Procedure:

- a) Priority is to dam and contain flowing spills.
- b) Use spill kits booms if available or use any material available; including but not limited to, nearby sand, dirt, landscaping materials, etc.
- c) Hazardous or unknown waste material spills
 - 1. Critical Emergency constitutes large quantities of flowing uncontained liquid that will affect areas with people or reach storm drain systems. Generally burst or tipped tanks. Call HAZMAT, Department of Water Quality, Utah County Health Department, and American Fork City.
 - 2. Minor Emergency constitutes a spill that has reached a storm drain but is no longer flowing. Call Utah County Health Department, American Fork City
 - 3. Spills that are contained on the surface and do not meet the criteria for Critical and minor emergencies may be managed by the responsible implementation of this SOP.
 - 4. Contact Numbers:

HAZMAT - 911

Department of Water Quality - 801-231-1769, 801-536-4123 Utah County Health Department - (801) 851-7000 American Fork City - (801) 763-3000

3. Cleanup Procedure:

- a) NEVER WASH SPILLS TO THE STORM DRAIN SYSTEMS.
- b) Clean per SDS requirements but generally most spills can be cleaned up according to the following:
 - Absorb liquid spills with spill kit absorbent material, sand or dirt until liquid is sufficiently converted to solid material.

- Remove immediately using dry cleanup methods, e.g. broom and shovel, or vacuum operations.
- Cleanup with water and detergents may also be necessary depending on the spilled material. However, the waste from this operation must be vacuumed or effectively picked up by dry methods. See Pavement Washing SOP.
- Repeat process when residue material remains.

4. DISPOSAL:

- a) Follow SDS requirements but usually most spills can be disposed per the following b. & c.
- b) Generally most spills absorbed into solid forms can be disposed to the dumpster and receptacles. Follow Waste Management SOP.
- c) Generally Liquid waste from surface cleansing processes may be disposed to the sanitary sewer system after the following conditions have been met:
 - Dry cleanup methods have been used to remove the bulk of the spill and disposed per the Waste Management SOP.
 - The liquid waste amounts are small and diluted with water. This is intended for spill cleanup waste only and never for the disposal of unused or spent liquids.

5. Documentation:

a) Document all spills in Appendix C.

6. SDS sheets:

a) SDS Manual is filed in break room.

7. Materials:

a) Generally sand or dirt will work for most clean up operations and for containment. However, it is the responsibility of the owner to select the absorbent materials and cleanup methods that are required by the SDS Manuals for chemicals used by the company.

8. Training:

APPENDIX C – RECORDKEEPING DOCUMENTS

MAINTENANCE/INSPECTION SCHEDULE

Erequency.*	Site/Infrastructure								
	Replace text with the infrastructure / system that must be maintained; repeat								
•									
• •									
	.*								
	N 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								


Inspection Frequency Key: A=annual, Q=Quarterly, M=monthly, W=weekly, S=following appreciable storm event, U=Unique infrastructure specific (specify)

RECORD INSPECTIONS IN THE MAINTENANCE LOG

Inspection Means: Either; Traditional walk through, Awareness/Observation, and during regular maintenance operations while noting efficiencies/inefficiencies/concerns found, etc.

MAINTENANCE LOG

Date≽	Maintenance Performed/SpilliEvents - Perform	Observation Notes including but not limited to: Inspection results, Observations, System Performance (effectiveness/inefficiencies), SOP Usefulness, Concerns, Necessary/Changes	Initials
		more and an experience of the second	
	· · · · · · · · · · · · · · · · · · ·		
	· · · · · · · · · · · · · · · · · · ·		
	· · · · · · · · · · · · · · · · · · ·		



^{*}You may create your own form that provides this same information or request a word copy of this document.

Annual SOP Training Log per Section 2

SOP	Trainer 3	Employee Name / Maintenance Contractor Co	Date
	,		
		·	

^{*}You may create your own form that provides this same information or request a word copy of this document.

Exhibit C

Exhibit D

Facility Operation and Maintenance Inspection Report for Storm Drain Facilities										
Inspector Name:			Subdivision Name:							
Inspection Date:						Address:				
Free	quency of inspection	□ Weekly			Monthly		□ Quarterly		□ Annual	
			Checked		Maintenance					
	Item Inspected	d .	Yes	No	Req'd	Not Req'd		Observations and Remark		
				Pond	Facilities					
1	Landscaping ma					<u> </u>				
2	Remove sedime	entation					<u> </u>			
3	Remove de						Ц		· · · · · · · · · · · · · · · · · · ·	
4	Repair side s									
5	Repair rip-rap p									
6	Repair control s									<u> </u>
7	Cleaning of c		<u> </u>							·
8	Removal of floats									
9	Maintenance o						1	· .		
10	Maintenance of	f outlets			<u> </u>	L				
			<u>S</u>	torm o	lrain syste	m				
Remove sediment from catch basins		from catch								
2 Cleaning storm drain pipes						1				
3 Maintenance of drainage swales						1				
4	Remove sediment from									
5	Remove sediment									
6.	Repair oil/ water						1			
7	Repair sand									
	• • • • • • • • • • • • • • • • • • • •		rking	lot and	l roads ma	intenan	ce			
1	Sweeping of pa									
2	Sweeping of						Т			
3	Cleaning of garbag	ge enclosure								
4	Cleaning of non-haz	ardous spills								
5										
6								·		
7	Removal of grass mowing									
supe the ii dir	certify under penalty of rvision in accordance nformation submitted ectly responsible for go f, true, accurate, and co includi	with a system d Based on my in athering the inf	lesigned quiry of formation ware the	d to ens f the po on, the nat ther	sure that querson or pe information e are signi	ualified persons we on provid ificant pe	perso ho m led is enalt	onnel properly canage the syste s to the best of ies for submitti	gather and evalu em, or those perso my knowledge an	ons id
					- .	•				

Approved as to form: Attorney for American Fork City

Site Inspector